

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION****Craig's Custom Motorcycles Inc.**3300 E. Harrisburg Pike
Middletown, Pa. 17057

Phone:717-944-9141

Fax:717-944-9452

Emergency Telephone: 1-800-424-9300 (24 hours, CHEMTREC)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS Number	%	OSHA		TWA		STEL		Ceiling	
			ACGIH	ppm	mg/m3	ppm	mg/m3	ppm	mg/m3	
Bisphenol A/Epichlorohydrin Based Epoxy Resin	025068-38-6	90 - 100								

3. HAZARDS IDENTIFICATION

Effects of Overexposure Repeated contact or breathing of vapors may cause irritation; material is also a strong sensitizer. Eye and skin contact may cause transient irritation.

4. FIRST AID MEASURES

Eyes	Flush with water, get medical attention.
Skin	Wash with soap and water; remove contaminated clothing.
Inhalation	Remove to fresh air.
Ingestion	No known antidote but give milk or water; induce vomiting if large amount swallowed.

5. FIREFIGHTING MEASURES

Flashpoint	> 480°F
Flashpoint Method	PMCC
Extinguishing Media	Dry chemicals, chemical foam, carbon dioxide, water.
Special Firefighting Measures	Avoid breathing smoke. Addition of water may reduce flame intensity.
Fire and Explosion Hazards	Toxic gases may be liberated; handle as combustible; store in a cool place.
Flammable Limits	N/A
LEL	N/A
UEL	N/A

6. ACCIDENTAL RELEASE MEASURES

Spill and Leak Procedures	Prevent skin and eye contact. Soak up in absorbent material or scrape up and transfer to disposal container. Wipe up remaining residue with solvents observing solvent flammability cautions, or use detergents.
---------------------------	--

7. HANDLING AND STORAGE

Handling and Storage	For industrial use only. WARNING: May cause sensitization, irritation or other allergic responses. Avoid eye and/or skin contact and prolonged inhalation of vapors.
Special Sensitivity	Store in a cool place in closed containers. Handle per Hazard Potential of hardener.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

responses. Avoid eye and/or skin contact and prolonged inhalation of vapors.

Special Sensitivity

Store in a cool place in closed containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Local Exhaust	Recommended
Mechanical Exhaust	Recommended
Eye Protection Requirements	Safety glasses or goggles
Glove Requirements	Required
Other Protection	As required to prevent all body contact, eye bath and/or safety shower.
Respirator Requirements	Air supplied or organic canister, mask in confined areas.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor	Straw Yellow, ammoniacal odor.
Boiling Point (°F)	> 374
Solubility in Water	partial
Specific Gravity (H ₂ O=1)	1.1
Evaporation Rate (BuAc=1)	ND
Vapor Pressure (mm Hg.)	< 1
Vapor Density (air = 1)	ND
Percent Volatile	< 1

10. STABILITY AND REACTIVITY

Stability	Stable
Conditions to Avoid (Stability)	Avoid contact with metals corroded by liquid amines; avoid high temperatures.
Incompatibility (Materials to Avoid)	Strong acids and bases, strong oxidizing agents.
Hazardous Decomposition Products	Carbon monoxide, carbon dioxide, aldehydes, phenol.
Hazardous Polymerization	Will Not Occur
Conditions to Avoid (Reactivity)	Chlorinated compounds; exotherms when used to cure epoxy resin.

11. TOXICOLOGICAL INFORMATION

Primary Entry Route(s)	Skin, eyes, inhalation.
Oral, LD50	> 1080 mg/kg
Dermal, LD50	> 1090 mg/kg

12. ECOLOGICAL INFORMATION

Not available

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods	Dispose of as hazardous waste according to local, state and federal regulations. Disposal method can be land burial or chemical incineration as regulated by all governmental agencies.
------------------------	---

14. TRANSPORTATION INFORMATION

Not Applicable

15. REGULATORY INFORMATION

TSCA: All components are on the TSCA inventory.

The information given and the recommendations made herein apply to our product(s) alone and are not combined with other product(s). Such are based on our research and on data from other reliable sources and are believed to be accurate. no guaranty of accuracy is made. it is the purchaser's responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.

16. OTHER INFORMATION

MSDS Date: 6/25/2002

Revision: B

HMIS Coding: H: 1 F: 1 R: 0